




SPECIFICATIONS

| Size | Metric | British |
|----------------------------------|--------------|-----------------|
| Max. Working Height(Indoor) | 8.00m | 26ft 3in |
| Max. Working Height(Outdoor) | 8.00m | 26ft 3in |
| Max. Platform Height(Indoor) | 6.00m | 19ft 8in |
| Max. Platform Height(Outdoor) | 6.00m | 19ft 8in |
| Overall Length G | 2.48m | 8ft 2in |
| Overall Width D | 1.15m | 3ft 9in |
| Overall Height(Rails Up) | 2.23m | 7ft 4in |
| Overall Height(Rails Down) | 1.70m | 5ft 7in |
| Platform Size(Length×Width) | 2.27m×1.12m | 7ft 5in×3ft 8in |
| Platform Extension Size 6 | 0.90m | 2ft 11in |
| Ground Clearance(Stowed/Raised) | 0.10m/0.019m | 4in/1in |
| Wheelbase (1) | 1.87m | 6ft 2in |
| Turning Radius(Inside/Outside) | 0m/2.20m | 0in/7ft 3in |
| Tyres | φ381×127mm | φ 1ft 3in×5in |

| Performance | | |
|--------------------------------|-------------|-------------|
| S.W.L | 544kg | 1199lb |
| S.W.L On Extension | 113kg | 250lb |
| Max. Occupants(Inside/Outside) | 2/2 | 2/2 |
| Gradeability | 25% | 25% |
| Travel Speed(Stowed) | 3.5km/h | 2.17mph |
| Travel Speed(Raised) | 0.8km/h | 0.50mph |
| Max. Working Slope | X-1.5°/Y-3° | X-1.5°/Y-3° |
| Up/Down Speed | 31/30sec | 31/30sec |

| Weight | | | |
|-----------------------------------|--------|--------|--|
| Overall Weight(Lead-acid Battery) | 1950kg | 4299lb | |

| Power | | |
|----------------|-------------|-------------|
| Hydraulic Tank | 20L | 5.3gal |
| Battery | 24V/185Ah | 24V/185Ah |
| Charger | 24V/30A | 24V/30A |
| Lifting Motor | 15VAC/3.5kW | 15VAC/3.5kW |
| | | |



ANSI A92.20, CSA B354.6.17





FEATURES

Standard Items

- Proportional Joystick Controls
- Self-Locking Gates
- One-Way Platform Extension Deck
- Drivable At Full Height
- Non-Marking Tyres
- Two-Wheel Drive
- Two-Wheel Steering
- Automatic Braking System
- Emergency Descent System
- Tubing Explosion-Proof System
- Onboard Fault Diagnostic System
- Tilt Alarm
- Motion Alarm
- Horn
- Hour Meter
- · Safety Arm For Troubleshooting
- Standard Transport Forklift Holes
- · Charging Protection System
- Flashing LED Beacon
- Foldable Guard Rails
- Automatic Pothole Protection
- Drive Enable
- Charging Indicator
- Manual Brake Release
- · Lanyard Attachment Point
- Tie-Down And Lifting Points
- Platform Load Sense System
- Emergency Stop Button



ZHEJIANG DINGLI MACHINERY CO., LTD.

Address: No.188 Qihang Road, Deging, Zhejiang P.R.C 313219

Telephone: +86(572)8681688 E-Mail: export@cndingli.com Https://en.cndingli.com











